

Hitac Chemicals Inc
1040 S. Milwaukee Ave. Suite 230, IL 60090
Tel: (224)522-8020; Fax: (224)836-5139

MATERIAL SAFETY DATA SHEET

TRANS-1,2-DICHLOROETHYLENE

Updated on 8/10/ 2009

1. Company Information

Hitac Chemicals Inc.
1040 S. Milwaukee Ave. Suite 230
Wheeling, IL 60090
Tel: 1-224-522-8020
Fax: 1-224-836-5139

For emergencies in the US, please call CHEMTREC: 800-424-9300 for help

2. Chemical Name: TRANS-1,2-DICHLOROETHYLENE

TRADE NAMES/SYNONYMS:

MTG MSDS 196; TRANS-ACETYLENE DICHLORIDE;
TRANS-DICHLOROETHYLENE; TRANS-1,2-DICHLOROETHENE;
1,2-DICHLOROETHYLENE; RCRA U079; C2H2CL2; MAT23670; RTECS KV9400000

CAS NUMBER: 156-60-5

3. HAZARDS IDENTIFICATION

NFPA RATINGS (SCALE 0-4): HEALTH=2 FIRE=3 REACTIVITY=2

EMERGENCY OVERVIEW:

COLOR: colorless
PHYSICAL FORM: liquid
ODOR: pleasant odor

MAJOR HEALTH HAZARDS:

respiratory tract irritation, skin irritation, eye irritation, central nervous system depression

PHYSICAL HAZARDS:

Flammable liquid and vapor. Vapor may cause flash fire. May react on contact with air, heat, light or water.

POTENTIAL HEALTH EFFECTS:

Page 2 of 7

INHALATION:

SHORT TERM EXPOSURE:

irritation, nausea, vomiting, drowsiness, symptoms of drunkenness

LONG TERM EXPOSURE:

no information on significant adverse effects

SKIN CONTACT:

SHORT TERM EXPOSURE: irritation

LONG TERM EXPOSURE: same as effects reported in short term exposure

EYE CONTACT:

SHORT TERM EXPOSURE: irritation

Hitac Chemicals Inc
1040 S. Milwaukee Ave. Suite 230, IL 60090
Tel: (224)522-8020; Fax: (224)836-5139

LONG TERM EXPOSURE: same as effects reported in short term exposure

INGESTION:

SHORT TERM EXPOSURE: symptoms of drunkenness

LONG TERM EXPOSURE: no information on significant adverse effects

4. FIRST AID MEASURES

INHALATION: If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.

SKIN CONTACT: Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

EYE CONTACT: Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

INGESTION: If vomiting occurs, keep head lower than hips to help prevent aspiration. If person is unconscious, turn head to side. Get medical attention immediately.

NOTE TO PHYSICIAN: For ingestion, consider gastric lavage. Consider oxygen.

5. FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS: Severe fire hazard. Vapor/air mixtures are explosive above flash point. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back.

EXTINGUISHING MEDIA: regular dry chemical, carbon dioxide, water, regular foam

Large fires: Use regular foam or flood with fine water spray.

FIRE FIGHTING: Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any

Page 3 of 7

discoloration of tanks due to fire. For tank, rail car or tank truck: Evacuation radius: 800 meters (1/2 mile).

Do not attempt to extinguish fire unless flow of material can be stopped first. Flood with fine water spray.

Do not scatter spilled material with high-pressure water streams. Cool containers with water spray until well after the fire is out. Apply water from a protected location or from a safe distance. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Water may be ineffective.

FLASH POINT: 36 F (2 C) (CC)

LOWER FLAMMABLE LIMIT: 9.7%

UPPER FLAMMABLE LIMIT: 12.8%

AUTOIGNITION: 860 F (460 C)

FLAMMABILITY CLASS (OSHA): IB

6. ACCIDENTAL RELEASE MEASURES

OCCUPATIONAL RELEASE:

Avoid heat, flames, sparks and other sources of ignition. Stop leak if possible without personal risk. Reduce vapors with water spray. Small spills: Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. Large spills: Dike for later disposal. Remove sources of ignition. Keep unnecessary people away, isolate hazard area and deny entry. Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304). If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424-8802 (USA) or (202)426-2675 (USA).

7. HANDLING AND STORAGE

STORAGE: Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.106. Grounding and bonding required. Keep separated from

Hitac Chemicals Inc
1040 S. Milwaukee Ave. Suite 230, IL 60090
Tel: (224)522-8020; Fax: (224)836-5139

incompatible substances.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE LIMITS:

TRANS-1,2-DICHLOROETHYLENE:

1,2-DICHLOROETHYLENE (ALL ISOMERS):

200 ppm (790 mg/m³) OSHA TWA

200 ppm ACGIH TWA

200 ppm (790 mg/m³) NIOSH recommended TWA 10 hour(s)

VENTILATION: Provide local exhaust ventilation system. Ventilation equipment should be explosionresistant if explosive concentrations of material are present. Ensure compliance with applicable exposure limits.

EYE PROTECTION: Wear splash resistant safety goggles with a faceshield. Provide an emergency eye

Page 4 of 7

wash fountain and quick drench shower in the immediate work area.

CLOTHING: Wear appropriate chemical resistant clothing.

GLOVES: Wear appropriate chemical resistant gloves.

RESPIRATOR: The following respirators and maximum use concentrations are drawn from NIOSH and/or OSHA.

2000 ppm

Any supplied-air respirator operated in a continuous-flow mode.

Any powered, air-purifying respirator with organic vapor cartridge(s).

Any air-purifying respirator with a full facepiece and an organic vapor canister.

Any air-purifying full-facepiece respirator (gas mask) with a chin-style, front-mounted or back-mounted organic vapor canister.

Any self-contained breathing apparatus with a full facepiece.

Any supplied-air respirator with a full facepiece.

Emergency or planned entry into unknown concentrations or IDLH conditions -

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positivepressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressuredemand or other positive-pressure mode.

Escape -

Any air-purifying full-facepiece respirator (gas mask) with a chin-style, front-mounted or back-mounted organic vapor canister.

Any appropriate escape-type, self-contained breathing apparatus.

For Unknown Concentrations or Immediately Dangerous to Life or Health -

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positivepressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressuredemand or other positive-pressure mode.

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	liquid
COLOR:	colorless
ODOR:	pleasant odor
MOLECULAR WEIGHT:	96.94
MOLECULAR FORMULA:	C ₂ H ₂ CL ₂
BOILING POINT:	118 F (48 C)
FREEZING POINT:	-58 F (-50 C)
VAPOR PRESSURE:	400 mmHg @ 31 C

Hitac Chemicals Inc
1040 S. Milwaukee Ave. Suite 230, IL 60090
Tel: (224)522-8020; Fax: (224)836-5139

VAPOR DENSITY (air=1): 3.34
SPECIFIC GRAVITY (water=1): 1.2565
WATER SOLUBILITY: slightly soluble
Page 5 of 7
PH: Not available
VOLATILITY: Not available
ODOR THRESHOLD: Not available
EVAPORATION RATE: Not available
COEFFICIENT OF WATER/OIL DISTRIBUTION: Not available
SOLVENT SOLUBILITY:
Soluble: ethanol, ether

10. STABILITY AND REACTIVITY

REACTIVITY:

May decompose on contact with air, light, moisture, heat or storage and use above room temperature. Releases toxic, corrosive, flammable or explosive gases.

CONDITIONS TO AVOID:

Avoid heat, flames, sparks and other sources of ignition. Containers may rupture or explode if exposed to heat. Keep out of water supplies and sewers.

INCOMPATIBILITIES: bases, metals, combustible materials, oxidizing materials, acids

HAZARDOUS DECOMPOSITION:

Thermal decomposition products: phosgene, halogenated compounds, oxides of carbon

POLYMERIZATION: May polymerize. Avoid contact with incompatible materials.

11. TOXICOLOGICAL INFORMATION

TRANS-1,2-DICHLOROETHYLENE:

IRRITATION DATA: 500 mg/24 hour(s) skin-rabbit moderate; 10 mg eyes-rabbit moderate

TOXICITY DATA: 24100 ppm inhalation-rat LC50; >5 gm/kg skin-rabbit LD50; 1235 mg/kg oral-rat LD50

LOCAL EFFECTS:

Irritant: inhalation, skin, eye

ACUTE TOXICITY LEVEL:

Moderately Toxic: ingestion

Slightly Toxic: inhalation

TARGET ORGANS: central nervous system

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: respiratory disorders

MUTAGENIC DATA: Available.

REPRODUCTIVE EFFECTS DATA: Available.

12. ECOLOGICAL INFORMATION

ECOTOXICITY DATA:

INVERTEBRATE TOXICITY: <110000 ug/L 48 hour(s) (Mortality) Water flea (Daphnia magna)

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262.

Hazardous Waste Number(s): U079.

14. TRANSPORT INFORMATION

U.S. DOT 49 CFR 172.101:

Hitac Chemicals Inc
1040 S. Milwaukee Ave. Suite 230, IL 60090
Tel: (224)522-8020; Fax: (224)836-5139

PROPER SHIPPING NAME: Trichlorobenzenes, liquid
ID NUMBER: UN2321
HAZARD CLASS OR DIVISION: 6.1
PACKING GROUP: III
LABELING REQUIREMENTS: 6.1
CANADIAN TRANSPORTATION OF DANGEROUS GOODS:
SHIPPING NAME: Trichlorobenzenes, liquid
UN NUMBER: UN2321
CLASS: 6.1
PACKING GROUP/RISK GROUP: III

15. REGULATORY INFORMATION

U.S. REGULATIONS:

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4): Not regulated.

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.30): Not regulated.

SARA TITLE III SECTION 304 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.40): Not regulated.

SARA TITLE III SARA SECTIONS 311/312 HAZARDOUS CATEGORIES (40 CFR 370.21):

ACUTE: Yes

CHRONIC: No

FIRE: Yes

REACTIVE: Yes

SUDDEN RELEASE: No

SARA TITLE III SECTION 313 (40 CFR 372.65):

1,2-DICHLOROETHYLENE (ALL ISOMERS)

OSHA PROCESS SAFETY (29CFR1910.119): Not regulated.

Page 7 of 7

STATE REGULATIONS:

California Proposition 65: Not regulated.

CANADIAN REGULATIONS:

WHMIS CLASSIFICATION: Not determined.

NATIONAL INVENTORY STATUS:

U.S. INVENTORY (TSCA): Listed on inventory.

TSCA 12(b) EXPORT NOTIFICATION: Not listed.

CANADA INVENTORY (DSL/NDSL): Not determined.

16. OTHER INFORMATION

MSDS SUMMARY OF CHANGES

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

MATHESON TRI-GAS, INC. MAKES NO EXPRESS OR IMPLIED WARRANTIES, GUARANTEES OR REPRESENTATIONS REGARDING THE PRODUCT OR THE INFORMATION HEREIN, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR USE. MATHESON TRI-GAS, INC. SHALL NOT BE LIABLE FOR ANY PERSONAL INJURY, PROPERTY OR OTHER DAMAGES OF ANY NATURE, WHETHER COMPENSATORY, CONSEQUENTIAL, EXEMPLARY, OR OTHERWISE, RESULTING FROM ANY PUBLICATION, USE OR RELIANCE UPON THE INFORMATION HEREIN.